



MB-R800




ACCESSORIES


- RECOMMENDED SPARE PARTS KIT
- FIXED COUPLING
- LOW SET DRUM KIT
- FULL SET DRUM KIT
- DUST SUPPRESSION KIT
- HIGH OIL TEMPERATURE REDUCING DEVICE
- ROCK AND ASPHALT PICK KITS
- 24 MONTHS WARRANTY


SPECIFICATIONS


EQUIPMENT EQUIPMENT	≥ 10 ≤ 22 ton
WEIGHT	1,00 ton
CUTTING WIDTH	1015 mm
PICK FORCE	33900 N
SPEED/MIN. (min/max)	60/80 rpm
OUTPUT TORQUE	10000 Nm
PRESSURE	> 350 bar
BACK PRESSURE	< 4 bar
OIL FLOW RATE	200 - 300 l/min. <small>The hydraulic flow and pressure values must meet the required parameters.</small>
DRUM DIAMETER	600 mm


APPLICATION AREAS



TUNNELS



UTILITY
WORK



URBAN
JOB SITES


ROAD WORKS


PROFILING
OF ROCKS AND
CONCRETE WALLS


DEMOLITION


EXCAVATION
AND CREATION
OF FOUNDATIONS


AGRICULTURAL
AND FOREST
AREAS