
SHAFT SCREENER

MB-HDS314


M







1430 mm



SPECIFICATIONS

<u>_</u>	Recommended excavator	ton	13 - 20
	Recommended backhoe loader/loader*	ton	9 - 14
	Weight	ton	1,40
	Load capacity	m³	0,90
	Pressure	bar	230 - 280
	Oil flow rate**	I/min	100 - 160

* Please verify machine's Rated Operating Capacity.

** The minimum hydraulic flow rate value must be alongside the required operating pressure.

SHAFT KIT

KIT	ADJUSTMENT*	APPLICATION
RQ8/RQ20/RQ50 Sifting kit	8/20/50 mm	Sifting damp/dry soil Soil aeration
RM Mixer kit	-	Soil aeration Compost aeration Charcoal reduction Glass reduction Drywall reduction
RE8/RE16 Fine Sifting kit	8/16 mm	Sifting damp/dry soil
RC Compost kit	36,5 mm	Shredding foliage and small branches Composting

* Shafts in closed position.

ACCESSORIES

RQ8/RQ20/RQ50 Sifting kit	RM Mixer kit
RE8/RE16 Fine Sifting kit	RC Compost kit
Shaft holder	24 month warranty

APPLICATION AREAS

TUNNELS















