
BF 60.1


6

0

U.S.A.









www.mbamerica.com - info@mbamerica.com

"Small but for great needs"



The BF 60.1 crusher bucket, regardless of the crushing job, is able to work in urban construction sites and limited work spaces.

Suitable for excavators starting from 19,800 pounds, the BF 60.1 weighs a little over 3,300 pounds and has a load capacity of 0.80 cubic yards.

The mouth opening measures at 25 inches W by 21 inches H to ensure an optimal production rate from 9 cy/h to 26 cy/h, depending on the crushing output.



AREAS OF APPLICATION

DEMOLITION RECYCLING EXCAVATION ROAD WORKS

SPECIFICATIONS

U.S.A.

RECOMMENDED EXCAVATOR	LOAD CAPACITY	OPENING DIMENSIONS	OUTPUT SETTING	DIMENSIONS
≥ 19,800 lbs	0.80 cy	25" W in x 21" H in	≥ 0.75 in ≤ 4.5 in	70" x 39" x 45" H in
OIL FLOW	PRESSURE	COUNTER PRESSURE	WEIGHT	MAXIMUM PRODUCTION
26 gal/min.	3,046 PSI	< 145 PSI	3,307 lbs	26 cy/h

ACCESSORIES

RECOMMENDED SPARE PARTS KIT	FIXED COUPLER	QUICK FEMALE COUPLER	IRON SEPARATOR	HOUR METER
BF6010028	FC6010000	BF6010000	BF6010010	804MBNF01
			DUST SUPPRESSION KIT	OPTIONAL 24 MONTHS WARRANTY
			KNMBOOL-KNMBOOS- KNMBOOM	WA246010

The data provided above is not binding, as the manufacturer reserves itself the right to make improvements to its products at any time and with no advance notice. References to excavator weights are approximate and many may be subject to changes. Consider a 20% tolerance.