



MB-R500



500 mm



500 mm

820 mm

ACCESSORIES

- KIT ROTATION TOURELLE (NECESSITE LIGNE DE ROTATION)
- KIT LATÉRAL RÉGLAGE FRAISAGE
- KIT PICS ROCHE OU ASPHALTE
- ATTACHE
- KIT TRANSMISSION AUGMENTÉE
- KIT BRUMISATEUR
- KIT POUR COUVERTURE DE TAMBOUR
- KIT RÉDUCTION DES HAUTES TEMPÉRATURES
- TAMBOUR INTERCHANGEABLE LOW-SET
- TAMBOUR INTERCHANGEABLE FULL-SET
- GARANTIE 24 MOIS
- PIÈCES DE RECHANGE CONSEILLÉES



CARACTÉRISTIQUES TECHNIQUES

MACHINE OPÉRATRICE	  ≥ 3,5 ≤ 11 Ton
DEBIT D'HUILE (MIN)	60-120 l/min.
PRESSION MAXIMALE	> 200 bar
CONTRE-PRESSION DRAINAGE MAX	< 4 bar
COUPLE DE SORTIE	5000 Nm
EFFORT DE CISAILEMENT	19600 N
POIDS	0,3 Ton
TOURS/MIN.	80/120 min/max

DOMAINES D'APPLICATION

TUNNELS
ET GALERIES

CANALISATIONS

CHANTIERS
URBAINSTRAVAUX
ROUTIERSPROFILAGE DE MURS
EN ROCHER ET BÉTON
CARRIÈRES

DEMOLITIONS

EXCAVATIONS
DE TERRAIN ET
RÉALISATION DE
FONDATIONSESPACES
AGRICLES ET
FORESTIERS

The data provided above is not binding, as the manufacturer reserves itself the right to make improvements to its products at any time and with no advance notice.
References to excavator weights are approximate and many may be subject to changes.