



MB-R700

MB[®]
THE CRUSHING EVOLUTION



500 mm



930 mm

ACCESSORIES

- KIT PIÈCES DÉTACHÉES CONSEILLÉ
- ATTACHE
- TAMBOUR INTERCHANGEABLE LOW-SET
- TAMBOUR INTERCHANGEABLE FULL-SET
- KIT BRUMISATEUR
- KIT RÉDUCTION DES HAUTES TEMPÉRATURES
- KIT PICS ROCHE OU ASPHALTE
- GARANTIE 24 MOIS



CARACTÉRISTIQUES TECHNIQUES

MACHINE OPÉRATRICE	 ≥ 6 ≤ 13 Ton
DEBIT D'HUILE (MIN)	110-180 l/min.
PRESSION MAXIMALE	> 250 bar
CONTRE-PRESSION DRAINAGE MAX	< 4 bar
COUPLE DE SORTIE	5000 Nm
EFFORT DE CISAILEMENT	19600 N
POIDS	0,6 Ton
TOURS/MIN.	80/110 min/max

DOMAINES D'APPLICATION



TUNNELS
ET GALERIES



CANALISATIONS



CHANTIERS
URBAINS



TRAVAUX
ROUTIERS



PROFILAGE DE MURS
EN ROCHER ET BÉTON
CARRIÈRES



DEMOLITIONS



EXCAVATIONS
DE TERRAIN ET
RÉALISATION DE
FONDATIONS



ESPACES
AGRICOLLES ET
FORESTIERS

The data provided above is not binding, as the manufacturer reserves itself the right to make improvements to its products at any time and with no advance notice.
References to excavator weights are approximate and many may be subject to changes.

Rev. 2019 / 03



WWW.MBCRUSHER.COM