



MB-R800



ACCESSORIES

- KIT PIÈCES DÉTACHÉES CONSEILLÉ
- ATTACHE
- TAMBOUR INTERCHANGEABLE LOW-SET
- TAMBOUR INTERCHANGEABLE FULL-SET
- KIT BRUMISATEUR
- KIT RÉDUCTION DES HAUTES TEMPÉRATURES
- KIT PICS ROCHE OU ASPHALTE
- GARANTIE 24 MOIS



CARACTÉRISTIQUES TECHNIQUES

MACHINE OPÉRATRICE	 $\geq 10 \leq 22$ Ton
DEBIT D'HUILE (MIN)	200-300 l/min.
PRESSION MAXIMALE	> 350 bar
CONTRE-PRESSION DRAINAGE MAX	< 4 bar
COUPLE DE SORTIE	10000 Nm
EFFORT DE CISAILEMENT	33900 N
POIDS	1 Ton
TOURS/MIN.	60/80 min/max

DOMAINES D'APPLICATION



TUNNELS
ET GALERIES



CANALISATIONS



CHANTIERS
URBAINS



TRAVAUX
ROUTIERS



PROFILAGE DE MURS
EN ROCHER ET BÉTON
CARRIÈRES



DEMOLITIONS



EXCAVATIONS
DE TERRAIN ET
RÉALISATION DE
FONDACTIONS



ESPACES
AGRICLES ET
FORESTIERS

The data provided above is not binding, as the manufacturer reserves itself the right to make improvements to its products at any time and with no advance notice.
References to excavator weights are approximate and many may be subject to changes.

Rev. 2019 / 03



WWW.MBCRUSHER.COM