



# MB-G1500 S2



## ACCESSORIES

- ATTACHE
- KIT MULTIPLICATEUR DE FORCE ROTATION (DÉBIT DE ROTATION 40 ÷ 70 L/MIN)
- KIT AMÉLIORATION PRÉHENSION INTERNE DES PINCES
- KIT DE LAMES EXTERNES PLUS ROBUSTES MULTIFONCTION
- KIT SOULÈVEMENT BASCULANT AVEC PROFILS EN CAOUTCHOUC
- KIT COUVERTURE CONFINEMENT PINCES
- KIT PIÈCES DE RECHANGE
- GARANTIE 24 MOIS

## CARACTÉRISTIQUES TECHNIQUES

MACHINE OPÉRATRICE	 ≥ 20 ≤ 30 Ton
CAPACITÉ DE CHARGEMENT (GRIFFES FERMÉES)	1,43 m <sup>3</sup> / 1430 L
DEBIT DE ROTATION	20 ÷ 35 l/min.
DEBIT D'HUILE (OUVERTURE/ FERMETURE)	70 l/min.
PRESSION DE ROTATION	> 220 bar
PRESSION (OUVERTURE/FERMETURE)	300 ÷ 400 bar
POIDS	2 Ton
ROTATION	360°



## DOMAINES D'APPLICATION



DEMOLITIONS



CHANTIERS  
URBAINS



PORTS ET  
TERMINAUX DE  
MARCHANDISES



carrières



CENTRES DE  
RECYCLAGE



DÉPLACEMENT  
ET SÉPARATION  
MATÉRIAUX

The data provided above is not binding, as the manufacturer reserves itself the right to make improvements to its products at any time and with no advance notice. References to excavator weights are approximate and many may be subject to changes.

Rev. 2019 / 03



WWW.MBCRUSHER.COM