



MB-R800

MB[®]
THE CRUSHING EVOLUTION




ACCESSORIES

- RECOMMENDED SPARE PARTS KIT
 - FIXED COUPLING
 - LOW SET DRUM KIT
 - FULL SET DRUM KIT
 - DUST SUPPRESSION KIT
 - HIGH OIL TEMPERATURE REDUCING DEVICE
 - ROCK AND ASPHALT PICK KITS
 - WARRANTY EXTENSION
- GOLD 24



SPECIFICATIONS

EQUIPMENT	 $\geq 22,000 \leq 48,500$ lbs
RECOMMENDED OIL FLOW (MIN)	53 - 79 gal/min
PRESSURE	> 5,076 PSI
COUNTER PRESSURE	< 58 PSI
OUTPUT TORQUE	10,000 Nm
PICK FORCE	25,003 ft lb
WEIGHT	2,205 lbs
SPEED/MIN. (MIN/MAX)	60 RPM/80 RPM

AREAS OF APPLICATION



TUNNELS



UTILITY
WORK



URBAN
JOB SITES



ROAD WORK



STONE AND
CONCRETE WALL
PROFILING



DEMOLITION



EXCAVATION AND
FOUNDATION
WORK



AGRICULTURAL
AND FOREST
AREAS

The data provided above is not binding, as the manufacturer reserves itself the right to make improvements to its products at any time and with no advance notice. References to excavator weights are approximate and many may be subject to changes.