



MB-G1200 S2

MB[®]
THE CRUSHING EVOLUTION




ACCESSORIES

- RECOMMENDED SPARE PARTS KIT
- FIXED COUPLING
- ROTATION POWER EXTENDER KIT
(ROTATION FLOW RATE 40 ÷ 70 L/MIN)
- GRIP IMPROVEMENT KIT
- MULTI-PURPOSE BLADE KIT
- RUBBER PROTECTION KIT
- CLAM SHELL KIT
- WARRANTY EXTENSION
GOLD 24



SPECIFICATIONS

EQUIPMENT	 $\geq 39,700 \leq 66,100$ lbs
LOAD CAPACITY (CLAWS CLOSED)	25 ft ³
FLOW DIRECTION	5 - 9 gal/min
OIL FLOW (OPEN/CLOSE)	19 gal/min
PRESSURE OF ROTATION	> 3,191 PSI
PRESSURE (OPEN/CLOSE)	4,351 PSI/5,802 PSI
WEIGHT	3,527 lbs
ROTATION	360°

AREAS OF APPLICATION



DEMOLITION



URBAN
CONSTRUCTION
SITES



PORTS AND
FREIGHT
TERMINALS



QUARRIES



RECYCLING AND
WASTE SORTING
FACILITY

The data provided above is not binding, as the manufacturer reserves itself the right to make improvements to its products at any time and with no advance notice. References to excavator weights are approximate and many may be subject to changes.