
MB-G1500 S2














ACCESSORIES

- RECOMMENDED SPARE PARTS KIT
- FIXED COUPLING
- ROTATION POWER EXTENDER KIT (ROTATION FLOW RATE 40 ÷ 70 L/MIN)
- GRIP IMPROVEMENT KIT
- MULTI-PURPOSE BLADE KIT
- RUBBER PROTECTION KIT
- CLAM SHELL KIT
- WARRANTY EXTENSION GOLD 24



SPECIFICATIONS

EQUIPMENT	≥ 44,100 ≤ 66,100 lbs
LOAD CAPACITY (CLAWS CLOSED)	50.5 ft3
FLOW DIRECTION	5 - 9 gal/min
OIL FLOW (OPEN/CLOSE)	19 gal/min
PRESSURE OF ROTATION	> 3,191 PSI
PRESSURE (OPEN/CLOSE)	4,351 PSI/5,802 PSI
WEIGHT	4,409 lbs
ROTATION	360°

AREAS OF APPLICATION





URBAN CONSTRUCTION SITES



PORTS AND FREIGHT TERMINALS



QUARRIES



RECYCLING AND WASTE SORTING FACILITY

The data provided above is not binding, as the manufacturer reserves itself the right to make improvements to its products at any time and with no advance notice.

References to excavator weights are approximate and many may be subject to changes.









