



MB-R500



ACCESSORIES

- CUTTER BODY ROTATION KIT (SECONDARY ROTATIONAL CIRCUIT REQUIRED)
- CUTTING DEPTH ADJUSTMENT KIT
- ROCK AND ASPHALT PICK KITS
- FIXED COUPLING
- POWER TRANSMISSION KIT
- DUST SUPPRESSION KIT
- DRUM COVER KIT
- HIGH OIL TEMPERATURE REDUCING DEVICE
- LOW SET DRUM KIT
- FULL SET DRUM KIT
- WARRANTY EXTENSION GOLD 24
- SUGGESTED SPARE PARTS KIT



SPECIFICATIONS

EQUIPMENT	≥ 7,700 < 24,200 lb
RECOMMENDED OIL FLOW (MIN)	16 - 32 gal/min
INLET MAXIMUM PRESSURE	> 5,076 PSI
DRAIN-OUT MAXIMUM PRESSURE	< 58 PSI
OUTPUT TORQUE	5,000 Nm
PICK FORCE	14,456 ft lb
WEIGHT	661 lbs
SPEED/MIN.	80 RPM/120 RPM

AREAS OF APPLICATION

TUNNELS	UTILITY WORK	URBAN JOB SITES	ROAD WORKS	PROFILING OF ROCKS AND CONCRETE WALLS	DEMOLITION	EXCAVATION AND CREATION OF FOUNDATIONS	AGRICULTURAL AND FOREST AREAS

The data provided above is not binding, as the manufacturer reserves itself the right to make improvements to its products at any time and with no advance notice. References to excavator weights are approximate and many may be subject to changes.