



MB-R800




ACCESSORIES









- RECOMMENDED SPARE PARTS KIT
- FIXED COUPLING
- LOW SET DRUM KIT
- FULL SET DRUM KIT
- DUST SUPPRESSION KIT
- HIGH OIL TEMPERATURE REDUCING DEVICE
- ROCK AND ASPHALT PICK KITS
- 24 MONTHS WARRANTY



SPECIFICATIONS

EQUIPMENT	 ≥ 22,000 < 48,500 lb
RECOMMENDED OIL FLOW (MIN)	53 - 79 gal/min
INLET MAXIMUM PRESSURE	> 5,076 PSI
DRAIN-OUT MAXIMUM PRESSURE	< 58 PSI
OUTPUT TORQUE	10,000 Nm
PICK FORCE	25,003 ft lb
WEIGHT	2,205 lbs
SPEED/MIN.	60 RPM/80 RPM

AREAS OF APPLICATION

							
TUNNELS	UTILITY WORK	URBAN JOB SITES	ROAD WORKS	PROFILING OF ROCKS AND CONCRETE WALLS	DEMOLITION	EXCAVATION AND CREATION OF FOUNDATIONS	AGRICULTURAL AND FOREST AREAS

The data provided above is not binding, as the manufacturer reserves itself the right to make improvements to its products at any time and with no advance notice. References to excavator weights are approximate and many may be subject to changes.